


— Est —
1962

IAN DICKIE

bitumen emulsion spraying machines



Direct-from-drum, manual and motorised Bitumen Emulsion Spraying Machines



ID10 CB

Visit www.iandickie.co.za to view
our full range of products

Measuring Success by Customer Satisfaction



bitumen emulsion spraying machines



IAN DICKIE MANUAL OR MOTORISED BITUMEN EMULSION SPRAYING MACHINES

▶ ID10M Manual Cold Bitumen Sprayer

The ID10 M can be used for both open areas and for patch work.

The hand operated pump is double acting with ball valves and an air chamber is incorporated to ensure an even and balanced discharge.

The flow is regulated by the stroke. It is of a special construction to handle cold bituminous emulsions and can be easily dismantled for maintenance.

The strainer is positioned to keep the pump fully primed when the operation is intermittent. Always ensure to flush the pump if being left to stand for any length of time.

The unit comes on a robust steel chassis with 4 x semi-solid rubber tyred wheels and is suitable for a 210lt drum.

It comes complete with a spray lance with 3m of hose, control valve and 2 X 65° nozzles, a suction probe and hose.



▶ Drum Lifter

For easy and safe handling of hot and heavy bitumen emulsion drums.

▶ Specifications

Engine

3,7 kW air-cooled recoil start petrol engine with 6:1 reduction gear. Output speed governed to approximately 500 r.p.m.

Filter

Washable stainless steel mesh filter element.

Pump

Gear type pump, direct drive from output shaft of engine reduction gear through a flexible coupling. Output when spraying bitumen emulsion is approximately 18lt per minute.

Lance

5m oil-resistant delivery hose fitted to 2m lance including handle grip, shut-off valve and 2 x 65° flat spray adjustable nozzles.

Chassis

Of all steel robust design on four 350mm x 100mm semi-solid rubber tyred wheels and incorporating handle bar, splash guard, drum and lance carrying brackets.

▶ Model ID10CB

The popular ID10CB, motorised Cold Bitumen Emulsion Sprayer has the following advantages over hand-spraying methods:

- High production - many times the daily output of hand sprayers
- Greater economy through more even distribution
- Robust construction takes rough handling
- Sprays cold emulsion with ease
- High efficiency cuts labour costs
- Light, manoeuvrable, compact
- Eliminates 'spotting'
- Gives smooth, even spray
- Easily transportable
- No operator fatigue

▶ ID10HB Hot Bitumen Emulsion Sprayer

The ID10HB offers the following additional features to the ID10CB Cold Bitumen Emulsion Sprayer:

- Ideally sized burner ring
- Full turntable steering incorporating towbar and handle for easy on site manoeuvrability
- Gas regulator
- Air control valve
- Heat deflector shield
- Gas bottle carrying bracket

▶ ID10HB Mobile Drum Heater and Transporter

- For pre-heating Bitumen Emulsion Drums
- Raises temp by 15 - 20 degrees C in same time it takes to spray out a 210lt drum
- The ideal complement to the ID10CB Cold Bitumen Emulsion sprayer for increased production.

▶ Unique Bypass System

When operating near kerbs or other structures which need to be kept clean, the built-in bypass system allows the spray to be instantly cut off or reduced by recycling all or part of the liquid delivered by the pump back to the inlet side of the pump.



Cape Town
TEL:(021) 534-3431

Johannesburg
TEL:(011) 609-4130

Port Elizabeth
TEL:(041) 451-1577

Durban
TEL:(031) 700-5636

Botswana
TEL:(+267) 391-4491

WITH OUR POLICY OF PRODUCT IMPROVEMENT WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS

